

View Online at <https://aerobasegroup.com/nsn/5935-01-249-1866>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape w/screw locks

Overall Length:

3.426 inches

Overall Height:

1.005 inches

Overall Width:

0.335 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end and glass fiber single mating end or plastic polyphenylene single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1, grade c military specification 1st treatment response single mating end single contact grouping and 11-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single material response single mating end single contact grouping or qq-w-321 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f or type gdi-30f military specification all material responses single mating end or mil-m-24519, type gpt-30f military specification all material responses single mating end or mil-p-46174, class 40, grade e military specification all material responses single mating end

Included Contact Quantity:

92 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.092 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.