Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-249-7555



Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

2.469 inches

Overall Diameter:

2.016 inches

Cable Entrance Diameter:

1.062 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Fk-I32 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

30.0 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

225.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

End Application:

General ground use, special or combinations of types, maintenance and/or test assemblies an/gsm-285

Thready Qty Per Inch (tpi):

6

Thread Size:

1.812 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

NSN 5935-01-249-7555

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment: Silver single mating end all contact groupings **Insert Material:** Plastic single mating end and plastic phenolic single mating end **Contact Surface Treatment Specification:** Qq-s-365 federal specification single treatment response single mating end all contact groupings **Terminal Type:** Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 7 single mating end 1st contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.032 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Un Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0