NSN 5935-01-249-8253

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-249-8253

Body Style:

Straight shape, internal coupling

Overall Length:

1.031 inches

Overall Diameter:

0.219 inches

Environmental Protection:

Corrosion resistant and shock resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

0.110 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

335.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

4000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Detent

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

NSN 5935-01-249-8253

Electrical Plug Connector - Page 2 of 2



Sł	nell Material:
Сс	opper alloy
Sł	hell Surface Treatment:
G	old
Sł	nell Material Specification:
Q	q-b-626, comp 360 federal specification single material response
In	sert Material Specification:
Mi	il-p-19468 military specification single material response single mating end
In	cluded Contact Quantity:
1 :	single mating end single contact grouping
In	cluded Contact Type:
Co	paxial socket single mating end single contact grouping
Pr	recious Material And Location:
Co	ontact surface and body surfaces gold
Pr	recious Material And Weight:
0.	105 gold grains, troy
Pr	recious Material:
G	old
Sł	nelf Life:
N/	'a
Uı	nit Of Measure:
De	emilitarization:
No	0
Fi	ig:
A	039b0
M	il-std (military Standard):
Mi	il-g-45204 spec.