

View Online at <https://aerobasegroup.com/nsn/5935-01-249-8259>

Body Style:

Right angle type

Overall Length:

5.000 inches

Overall Width:

0.406 inches

Body Height:

0.330 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and thermal shock resistant and vibration proof

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

0.6 megahertz single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-c-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2 federal specification 2nd treatment response single mating end single contact grouping or mil-c-26074, class 1 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613d, comp 260 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 9 oclock

Shell Material:

Aluminum alloy 6061 or aluminum alloy 6063

Shell Surface Treatment:

Chromate

Shell Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Shell Material Specification:

Qq-a-200/9b federal specification single material response or qq-a-200/9b federal specification single material response

Insert Material Specification:

Mil-m-20693, type 1 military specification single material response single mating end

Included Contact Quantity:

90 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.090 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-45204 spec.