

View Online at <https://aerobasegroup.com/nsn/5935-01-249-9387>

Body Style:

Round flange mount w/lockin

Overall Length:

1.620 inches

Bushing Diameter:

0.500 inches

Mounting Hole Circle Radius:

0.600 inches

Overall Diameter:

1.500 inches

Environmental Protection:

Heat resistant and cold resistant

Unthreaded Mounting Hole Diameter:

0.170 inches

Distance From Mounting Shoulder To Rear Face:

1.370 inches

Mating End Quantity:

1

Contact Maximum Frequency Rating:

400.0 megahertz single mating end single contact grouping

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

End Application:

Electrical surge

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Beryllium single mating end single contact grouping and copper alloy 173 single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Contact Surface Treatment Specification:

Qq-s-365, type i or ii, grade a federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, alloy 173, cond h, heat treat to cond ht federal specification single material response single mating end single contact grouping

Shell Material:

Metal

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290, class 2 federal specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Nuclear Hardness Critical Feature:

Hardened

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0