NSN 5935-01-249-9647

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-249-9647

Body Style:
Straight shape
Overall Length:
2.078 inches
Overall Width:
0.492 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
25 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Connector Cable Strain Relief Method:
Bracket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass fiber single mating end and plastic polycarbonate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Terminal Type:
Insulation piercing single mating end single contact grouping
Shell Material:
Plastic
Included Contact Quantity:

25 single mating end single contact grouping

NSN 5935-01-249-9647

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-g-45204 spec.

A039b0