## NSN 5935-01-250-1506

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-250-1506

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
41.1 millimeters
Overall Diameter:
37.4 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
17-8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
110.0 and 250.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Length:
0.219 inches
Thready Qty Per Inch (tpi):
20
Thread Size:
0.938 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

## **NSN 5935-01-250-1506**Electrical Plug Connector - Page 2 of 2



Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium	
Shell Surface Treatment Specification:	
Qq-p-416 federal specification single treatment response	
Included Contact Quantity:	
8 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.008 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification ty	ype data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type	e data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.	).
Thread Series Designator:	
Unef	
Specification Data:	
81349-dod-c-38999/47 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	