## NSN 5935-01-250-2524

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-250-2524

| View Online at https://aerobasegroup.com/nsn/5935-01-250-2524  |
|--|
| Thread Direction:  |
| Right-hand and right-hand  |
| Body Style:  |
| Straight shape, internal coupling  |
| Overall Length:  |
| 33.2 millimeters   |
| Overall Diameter:  |
| 48.0 millimeters   |
| Threaded Device Type:  |
| Back shell and coupling facility   |
| Mating End Quantity:   |
| 1  |
| Contact Removability:  |
| Removable single mating end single contact grouping  |
| Polarization Method:   |
| Keyway or multiple keyway  |
| Insert Position In Deg:  |
| 0.0  |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
| Internally threaded coupling ring  |
| Thread Size:   |
| 37.0 millimeters and 37.0 millimeters  |
| Thread Pitch In Millimeters:   |
| 1.00 and 1.00  |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Contact Surface Treatment Specification:   |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type:   |
| Crimp single mating end single contact grouping  |
| Shell Material:  |
| Aluminum alloy   |
| Shell Surface Treatment:   |
| Cadmium  |
| Shall Surface Treatment Specification.   |

**Shell Surface Treatment Specification:** 

Qq-p-416 federal specification single treatment response

## **NSN 5935-01-250-2524**Electrical Plug Connector - Page 2 of 2



| Thread Tolerance Class:  6g external and 6h internal   |      |
|--|------|
| 6g external and 6h internal  |      |
|  |      |
| Included Contact Quantity:   |      |
| 29 single mating end single contact grouping   |      |
| Included Contact Type:   |      |
| Round socket single mating end single contact grouping   |      |
| Precious Material And Location:  |      |
| Contact surfaces gold  |      |
| Precious Material And Weight:  |      |
| 0.029 gold grains, troy  |      |
| Precious Material:   |      |
| Gold   |      |
| Test Data Document:  |      |
| 81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification | atio |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |      |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |      |
| Thread Series Designator:  |      |
| Iso m and iso m  |      |
| Specification Data:  |      |
| 81349-dod-c-38999/26 government specification  |      |
| Shelf Life:  |      |
| N/a  |      |
| Unit Of Measure:   |      |
|  |      |
| Demilitarization:  |      |
| No   |      |
| Fiig:  |      |
| A039b0   |      |
| Mil-std (military Standard):   |      |
| Mil-g-45204 spec.  |      |