

View Online at <https://aerobasegroup.com/nsn/5935-01-250-8896>

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

34.16 millimeters

**Overall Height:**

Between 42.3 millimeters and 43.4 millimeters

**Overall Width:**

Between 42.3 millimeters and 43.4 millimeters

**Unthreaded Mounting Hole Diameter:**

Between 3.6 millimeters and 4.0 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

34.9 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

34.9 millimeters

**Distance From Mounting Shoulder To Front Face:**

Between 19.2 millimeters and 20.8 millimeters

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

23-21 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Detent

**Thread Size:**

34.0 millimeters

**Thread Pitch In Millimeters:**

1.00

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Nickel

**Shell Surface Treatment Specification:**

Mil-c-26074 military specification single treatment response

**Thread Tolerance Class:**

6g external

**Included Contact Quantity:**

21 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.021 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Iso m

**Specification Data:**

81349-dod-c-38999/40 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26074 spec.