NSN 5935-01-250-9917

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-250-9917



Thread Class: 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.500 inches **Overall Height:** 0.680 inches **Overall Width:** 0.344 inches **Distance Between Mounting Facility Centers:** 1.250 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thread Length: 0.188 inches Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Glass single mating end and plastic diallyl phthalate single mating end

NSN 5935-01-250-9917

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

26 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.026 gold grains, troy and 0.026 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.