

View Online at <https://aerobasegroup.com/nsn/5935-01-251-2809>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, external/internal coupling

**Overall Length:**

0.686 inches

**Overall Height:**

0.713 inches

**Overall Width:**

0.312 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sma all mating ends

**Contact Removability:**

Removable all mating ends single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

335.0 all mating ends single contact grouping

**Contact Maximum Frequency Rating:**

18000.0 megahertz all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, gr c, cl 2 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550, class 4 military specification 2nd treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Gold and nickel

**Shell Surface Treatment Specification:**

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response and mil-c-26074, cl 1 military specification 2nd treatment response

**Shell Material Specification:**

Ams-5640, type 303 assn standard single material response

**Insert Material Specification:**

L-p-403 federal specification single material response all mating ends

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial pin all mating ends single contact grouping

**Precious Material And Location:**

Contact and body surfaces gold

**Precious Material And Weight:**

0.110 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.