## NSN 5935-01-251-4932

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-251-4932

**Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Overall Length:** 0.447 inches **Overall Diameter:** 0.406 inches **Distance From Mounting Shoulder To Front Face:** 0.290 inches **Threaded Device Type:** Coupling facility and mounting hole **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping **Contact Maximum Frequency Rating:** 10000.0 megahertz single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 36 and 80 **Thread Size:** 0.250 inches and 0.060 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Metal single mating end single contact grouping **Terminal Type:** Turret single mating end single contact grouping **Shell Material:** Metal **Included Contact Quantity:** 

Included Contact Type:

Coaxial socket single mating end single contact grouping

1 single mating end single contact grouping

## NSN 5935-01-251-4932

Electrical Receptacle Connector - Page 2 of 2



Thread Series Designator:
Uns and unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A039b0