NSN 5935-01-251-5044

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-251-5044

| Body Style: |
|---|
| Straight type |
| Overall Length: |
| 2.010 inches |
| Overall Width: |
| 0.317 inches |
| Body Height: |
| 0.370 inches |
| Environmental Protection: |
| Cold resistant and heat resistant |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 2 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 1.0 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end and glass fiber single mating end |
| Terminal Type: |
| Pin single mating end single contact grouping |
| Included Contact Quantity: |
| 34 single mating end single contact grouping |
| Included Contact Type: |
| Flat pin single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.034 gold grains, troy |

Gold

Precious Material:

NSN 5935-01-251-5044

Electrical Receptacle Connector - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A039b0