

View Online at <https://aerobasegroup.com/nsn/5935-01-251-8000>

Body Material:

Plastic

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Bottom surface mount

Overall Length:

1.400 inches

Overall Height:

0.675 inches

Overall Width:

0.440 inches

Mounting Hole Diameter:

0.138 inches

Distance Between Mounting Facility Centers:

0.960 inches

Mounting Hole Style:

Two mounting holes/slots, in-line

Contact Maximum Current Rating In Amps:

10.0

Contact Material:

Beryllium copper

Contact Surface Treatment:

Gold

Accommodated Contact Quantity:

2

End Application:

4austin ship class lpd-4 amphibious transport docks, tarawa class lha, nimtz class cvn, virginia class cgn (41), whidbey island class lsd, forrestal class cv, supply class aoe, oliver perry class ffg, safeguard class ars, spruance class dd (963)

Projection Length Above Mounting Surface:

0.241 inches

Mounting Method:

Threaded hole

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

In-line

Criticality Code Justification:

Feat

Ground Terminal Type And Quantity:

1 tab, solder lug

Special Features:

Weapon system essential

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300