

View Online at <https://aerobasegroup.com/nsn/5935-01-251-8000>

**Body Material:**

Plastic

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Bottom surface mount

**Overall Length:**

1.400 inches

**Overall Height:**

0.675 inches

**Overall Width:**

0.440 inches

**Mounting Hole Diameter:**

0.138 inches

**Distance Between Mounting Facility Centers:**

0.960 inches

**Mounting Hole Style:**

Two mounting holes/slots, in-line

**Contact Maximum Current Rating In Amps:**

10.0

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Gold

**Accommodated Contact Quantity:**

2

**End Application:**

4austin ship class lpd-4 amphibious transport docks, tarawa class lha, nimitz class cvn, virginia class cgn (41), whidbey island class lsd, forrestal class cv, supply class aoe, oliver perry class ffg, safeguard class ars, spruance class dd (963)

**Projection Length Above Mounting Surface:**

0.241 inches

**Mounting Method:**

Threaded hole

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Contact Position Arrangement Style:**

In-line

**Criticality Code Justification:**

Feat

**Ground Terminal Type And Quantity:**

1 tab, solder lug

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.002 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02300