

View Online at <https://aerobasegroup.com/nsn/5935-01-251-8036>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

33.8 millimeters

**Overall Height:**

35.0 millimeters

**Overall Width:**

35.0 millimeters

**Environmental Protection:**

Fuel resistant and shock resistant and vibration resistant and waterproof

**Unthreaded Mounting Hole Diameter:**

Between 3.2 millimeters and 3.3 millimeters

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

27.0 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

27.0 millimeters

**Distance From Mounting Shoulder To Front Face:**

Between 23.1 millimeters and 23.5 millimeters

**Threaded Device Type:**

Back shell

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

18-19 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

240.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet slot

**End Application:**

4920-01-136-2857 test set, automated

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

1.000 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping and rhodium single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Included Contact Quantity:**

10 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver and contact surfaces rhodium

**Precious Material And Weight:**

0.010 gold grains, troy and 0.010 silver grains, troy and 0.010 rhodium grains, troy

**Precious Material:**

Gold and silver and rhodium

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0