Electrical Plug Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-251-8055

Tł	nread Class:
2a	
Tł	nread Direction:
Ri	ght-hand
B	ody Style:
St	raight shape, internal coupling
0	verall Length:
0.	766 inches
0	verall Diameter:
1.	281 inches
Tł	nreaded Device Type:
Ba	ack shell
Μ	ating End Quantity:
1	
C	ontact Position Arrangement Style:
16	3-26 single mating end
Po	plarization Method:
Ke	eyway or multiple keyway
In	sert Position In Deg:
0.	0 and 100.0 and 128.0 and 228.0 and 265.0
Sł	nell Type:
So	blid
C	onnector Locking Method:
Ba	ayonet latch
Er	nd Application:
T€	est set, guided missile an/dsm-156a
Tł	nread Length:
0.	219 inches
Tł	nready Qty Per Inch (tpi):
20	
Tł	nread Size:
0.	938 inches
SI	nell Material:
Al	uminum alloy
SI	nell Surface Treatment:
Ca	admium
SI	nell Surface Treatment Specification:
Q	q-p-416 federal specification single treatment response
T€	est Data Document:
81	349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
fo	rmat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	ivironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef



Specification Data:

96906-ms27473 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.