Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-251-8779

Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
34.16 millimeters
Overall Diameter:
26.78 millimeters
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
Afdx 11-5 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
100.0 and 260.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Size:
15.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium

# NSN 5935-01-251-8779

Electrical Plug Connector - Page 2 of 2



## Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

## Thread Tolerance Class:

6g external

## Included Contact Quantity:

5 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## Precious Material And Location:

Contact surfaces gold

## Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

### **Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

lso m

Specification Data:

81349-dod-c-38999/49 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.