

View Online at <https://aerobasegroup.com/nsn/5935-01-252-0214>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.310 inches

Overall Diameter:

0.780 inches

Environmental Protection:

Cold resistant and heat resistant and corrosion resistant and moisture resistant and shock resistant and vibration resistant

Threaded Device Type:

Coupling facility and coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc 2nd mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 2nd mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring and externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

24 and 28

Thread Size:

0.625 inches and 0.438 inches

Contact Material:

Copper alloy 360 all mating ends single contact grouping

Contact Surface Treatment:

Silver all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Material Specification:

Qq-b-626, 1/2 hard federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy 360

Shell Material Specification:

Qq-b-626, 1/2 hard federal specification single material response

Insert Material Specification:

L-p-403 federal specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.010 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0