NSN 5935-01-252-0218

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-252-0218 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 33.8 millimeters **Overall Height:** 41.0 millimeters **Overall Width:** 41.0 millimeters **Environmental Protection:** Fuel resistant and shock resistant and vibration resistant and waterproof **Unthreaded Mounting Hole Diameter:** 3.2 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 31.8 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 31.8 millimeters **Distance From Mounting Shoulder To Front Face:** 23.05 millimeters **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 22-14 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

NSN 5935-01-252-0218

A039b0

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Bayonet slot
End Application:
4920-01-136-2857 test set, automated ground engine
Thready Qty Per Inch (tpi):
18
Thread Size:
1.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping and rhodium single mating end single
contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, class 2, type 2 federal specification all treatment responses
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver and contact surfaces rhodium
Precious Material And Weight:
0.019 gold grains, troy and 0.019 silver grains, troy and 0.019 rhodium grains, troy
Precious Material:
Gold and silver and rhodium
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: