NSN 5935-01-252-0657

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-252-0657

| Body Style: |
|--|
| Wall type |
| Overall Height: |
| 1.203 inches |
| Overall Width: |
| 1.406 inches |
| Body Length: |
| 1.687 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.164 inches |
| Distance Between Mounting Facility Centers: |
| 1.937 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| "3, 6-15, 6-30" single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 15.0 single mating end all contact groupings |
| Contact Maximum Ac Voltage Rating In Volts: |
| 250.0 single mating end all contact groupings |
| Contact Maximum Dc Voltage Rating In Volts: |
| 250.0 single mating end all contact groupings |
| Polarization Method: |
| Contact |
| Connector Locking Method: |
| Friction |
| End Application: |
| 4930-01-208-6400 shop equip, gen purpose |
| Terminal Location: |
| Side single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Insert Material: |
| Plastic phenolic single mating end |
| Terminal Type: |
| Screw single mating end all contact groupings |
| Included Contact Quantity: |
| 2 single mating end 2nd contact grouping |
| |

Included Contact Type:

Flat socket single mating end 2nd contact grouping

NSN 5935-01-252-0657

Electrical Receptacle Connector - Page 2 of 2



| _ | | | - | | |
|---|----|----|---|-------|---|
| C | hο | 14 | | .ife | |
| • | | | _ | .II C | - |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0