NSN 5935-01-252-4554

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-252-4554

Body Style:

Straight shape

Overall Length:

1.050 inches

Overall Diameter:

1.031 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Mating End Quantity:

2

Contact Position Arrangement Style:

40515 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch and bayonet pin

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Rubber synthetic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-225 federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Round socket 1st mating end single contact grouping

NSN 5935-01-252-4554

Connector Adapter - Page 2 of 2

Special Features:



Dry lubricant inside coupling ring **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.010 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.