

View Online at <https://aerobasegroup.com/nsn/5935-01-252-6066>

Thread Direction:

Right-hand

Body Style:

Straight type

Overall Length:

6.220 inches

Overall Height:

0.667 inches

Overall Width:

0.366 inches

Environmental Protection:

Heat resistant and cold resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

5.900 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Thread Size:

2.5 millimeters

Thread Pitch In Millimeters:

0.45

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Glass single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and mil-p-27418 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550, cl x military specification 3rd treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Thread Tolerance Class:

6g external

Included Contact Quantity:

160 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.160 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Iso m

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.