

View Online at <https://aerobasegroup.com/nsn/5935-01-252-7793>

**Body Style:**

Right angle type

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end 1st contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

**Insert Material:**

Plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end 1st contact grouping

**Terminal Type:**

Pin single mating end 1st contact grouping

**Included Contact Quantity:**

60 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.060 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.