**Body Style:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-253-2435

# Straight shape, external coupling **Overall Length:** 34.1 millimeters **Overall Height:** Between 30.4 millimeters and 31.5 millimeters **Overall Width:** Between 30.4 millimeters and 31.5 millimeters **Unthreaded Mounting Hole Diameter:** Between 3.1 millimeters and 3.5 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 24.6 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 24.6 millimeters **Distance From Mounting Shoulder To Front Face:** Between 19.2 millimeters and 20.8 millimeters **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 110.0 and 250.0 Shell Type: Solid **Connector Locking Method:** Detent **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Nickel



# Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

#### **Included Contact Quantity:**

37 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.037 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-dod-c-38999/42 government specification

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-c-26074 spec.