Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-253-2785

# Body Style:

Straight shape, external coupling

### **Overall Length:**

34.1 millimeters

## **Overall Height:**

Between 39.1 millimeters and 40.2 millimeters

### **Overall Width:**

Between 39.1 millimeters and 40.2 millimeters

### **Unthreaded Mounting Hole Diameter:**

Between 3.1 millimeters and 3.5 millimeters

### Center To Center Distance Between Mounting Facilities Parallel To Height:

### 31.7 millimeters

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

31.7 millimeters

### **Distance From Mounting Shoulder To Front Face:**

Between 19.2 millimeters and 20.8 millimeters

### Mating End Quantity:

1

### **Contact Position Arrangement Style:**

21-35 single mating end

### **Contact Removability:**

Removable single mating end single contact grouping

### **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

110.0 and 250.0

### Shell Type:

Solid

### **Connector Locking Method:**

Detent

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### Shell Material:

Aluminum alloy

### Shell Surface Treatment:

Nickel



### Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

#### **Included Contact Quantity:**

79 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.079 gold grains, troy

#### **Precious Material:**

Gold

### **Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-dod-c-38999/42 government specification

### Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

#### \_...

Fiig:

A039b0

### Mil-std (military Standard):

Mil-c-26074 spec.