

View Online at <https://aerobasegroup.com/nsn/5935-01-254-0135>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.875 inches

Overall Diameter:

0.250 inches

Environmental Protection:

Shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.425 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

M 1st mating end

Contact Maximum Ac Voltage Rating In Volts:

300.0 1st mating end single contact grouping

Contact Maximum Frequency Rating:

4000.0 megahertz 1st mating end single contact grouping

Shell Type:

Solid

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 1st mating end single contact grouping

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Terminal Location:

Front 1st mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene all mating ends

Terminal Type:

Pin 1st mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365, type ii, grade a federal specification single treatment response

Precious Material And Location:

Body surface silver

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0