## NSN 5935-01-254-0612

Round pin single mating end single contact grouping

**Body Style:**Right angle type

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-254-0612

**Overall Length:** 1.196 inches **Overall Width:** 0.430 inches **Body Height:** 0.120 inches **Unthreaded Mounting Hole Diameter:** 0.064 inches **Distance Between Mounting Facility Centers:** 0.900 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end and glass fiber single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, ty mfh military specification all material responses single mating end **Included Contact Quantity:** 8 single mating end single contact grouping **Included Contact Type:** 

## NSN 5935-01-254-0612

Electrical Receptacle Connector - Page 2 of 2



Special	Features:
---------	-----------

Outside contacts removed from each end of connector; one hole drilled at each end of connector

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.008 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.