NSN 5935-01-254-0615

Electrical Receptacle Connector Body - Page 1 of 2



| Thread Class: | | | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|
| 2a and 2b and 2a | | | | | |
| Thread Direction: | | | | | |
| Right-hand and right-hand and right-hand | | | | | |
| Body Style: | | | | | |
| Rectangular shape | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | | |
| 1.969 inches | | | | | |
| Overall Height: | | | | | |
| 0.890 inches | | | | | |
| Overall Width: | | | | | |
| 1.688 inches | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | |
| 0.125 inches | | | | | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | | | | | |
| 0.500 inches | | | | | |
| Threaded Device Type: | | | | | |
| Coupling facility and mounting stud | | | | | |
| Mating End Quantity: | | | | | |
| 1 | | | | | |
| Contact Position Arrangement Style: | | | | | |
| 66 single mating end | | | | | |
| Polarization Method: | | | | | |
| Shell | | | | | |
| Shell Type: | | | | | |
| Solid | | | | | |
| | | | | | |
| Connector Locking Method: | | | | | |
| Connector Locking Method: Jackscrew-socket | | | | | |
| - | | | | | |
| Jackscrew-socket | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: 0.138 inches and 0.138 inches and 0.112 inches | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: 0.138 inches and 0.138 inches and 0.112 inches Insert Material: | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: 0.138 inches and 0.138 inches and 0.112 inches Insert Material: Plastic diallyl phthalate single mating end | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: 0.138 inches and 0.138 inches and 0.112 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material: | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: 0.138 inches and 0.138 inches and 0.112 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material: Aluminum | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: 0.138 inches and 0.138 inches and 0.112 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material: Aluminum Shell Surface Treatment: | | | | | |
| Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 32 and 40 Thread Size: 0.138 inches and 0.138 inches and 0.112 inches Insert Material: Plastic diallyl phthalate single mating end Shell Material: Aluminum Shell Surface Treatment: Anodize | | | | | |

Special Features:

Items furnished as accessories -mounting plate

NSN 5935-01-254-0615

Electrical Receptacle Connector Body - Page 2 of 2



| T | 'nr | ead | Series | Design | ator: |
|---|-----|-----|---------------|--------|-------|
| | | | | | |

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0