NSN 5935-01-254-1829

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-254-1829

Body Style: Straight shape, external coupling Overall Length: 1.626 inches Overall Diameter: 0.810 inches **Distance From Mounting Shoulder To Front Face:** 0.790 inches **Mounting Facility Thickness:** 0.187 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

Bushing Accommodation Hole Shape:

1 single mating end single contact grouping

Included Contact Quantity:

Round w/double flat

NSN 5935-01-254-1829

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Coaxial socket single ma
Precious Material And L

ting end single contact grouping

_ocation:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.