NSN 5935-01-254-2096

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-254-2096

Body Style:

Straight shape, external coupling

Overall Length:

34.1 millimeters

Overall Height:

Between 42.3 millimeters and 43.4 millimeters

Overall Width:

Between 42.3 millimeters and 43.4 millimeters

Unthreaded Mounting Hole Diameter:

Between 3.6 millimeters and 4.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Height:

34.92 millimeters

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

34.92 millimeters

Distance From Mounting Shoulder To Front Face:

Between 19.2 millimeters and 20.8 millimeters

Mating End Quantity:

1

Contact Position Arrangement Style:

23-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

100.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Detent

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

NSN 5935-01-254-2096

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
ncluded Contact Quantity:
100 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-dod-c-38999/42 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.