

View Online at <https://aerobasegroup.com/nsn/5935-01-254-4871>

Thread Class:

2g

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.703 inches

Overall Height:

Between 2.219 inches and 2.250 inches

Overall Width:

Between 2.219 inches and 2.250 inches

Unthreaded Mounting Hole Diameter:

Between 0.190 inches and 0.220 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.687 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.687 inches

Distance From Mounting Shoulder To Front Face:

1.005 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-333 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

8

Thread Size:

2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-s-365 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.061 gold grains, troy and 0.061 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.