

View Online at <https://aerobasegroup.com/nsn/5935-01-254-7729>

Body Style:

T-shape

Overall Length:

0.853 inches

Overall Height:

0.656 inches

Overall Width:

0.250 inches

Mating End Quantity:

3

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction and spring friction and spring friction

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550 military specification 2nd treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and copper

Shell Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket 3rd mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.115 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.