

View Online at <https://aerobasegroup.com/nsn/5935-01-255-2448>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.420 inches

Overall Diameter:

1.656 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

22-41 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

135.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Thread Length:

0.290 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.312 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response single mating end all contact groupings and qq-n-290, cl 2 federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy 6061 or aluminum alloy 380.0 or aluminum alloy a380.0

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-367, t6 federal specification single material response or qq-a-591 federal specification single material response or qq-a-591 federal specification single material response

Included Contact Quantity:

27 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Special Features:

In order to complete the connector assembly, the user must obtain/provide the backshell; standard versions may be ordered as nsn 5935-01-172-8574, p/n m85049/52-1-22w for the straight style, or nsn 5935-01-190-6817, p/n m85049/51-1-22w for the right angle style

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.041 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3475 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.