NSN 5935-01-255-5002

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-255-5002
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
0.850 inches
Overall Diameter:
0.248 inches
Environmental Protection:
Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant
Threaded Device Type:
Coupling facility and coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
Sma all mating ends
Contact Removability:
Nonremovable all mating ends single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell and internally threaded coupling nut
Thready Qty Per Inch (tpi):
36 and 36
Thread Size:
0.250 inches and 0.250 inches
Contact Material:
Copper alloy 172 all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping and copper all mating ends single contact grouping
Insert Material:
Plastic polytetrafluoroethylene all mating ends
Contact Surface Treatment Specification:
Mil-g-45204, type 2, gr c, cl 1 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550 military
specification 2nd treatment response all mating ends single contact grouping
Contact Material Specification:
Qq-c-530, 1/2 hard federal specification single material response all mating ends single contact grouping
Shell Material:
Stainless steel

Passivate

Shell Surface Treatment:

NSN 5935-01-255-5002

Connector Adapter - Page 2 of 2



Shell Surface Treatment Specification:

Mil-f-14072 military specification single treatment response

Shell Material Specification:

Astm-a-582-80 assn standard single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.