## NSN 5935-01-255-6147

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-255-6147 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.812 inches **Overall Diameter:** 0.282 inches **Environmental Protection:** Shock resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 2.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 335.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Crimp type **End Application:** Aircraft, galaxy c-5 Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.216 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-01-255-6147

Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping and qq-c-530 federal specification single
material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver and nickel
Shell Surface Treatment Specification:
Qq-s-365 federal specification 1st treatment response and qq-n-290 federal specification 2nd treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact surface gold and shell surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.100 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0

Mil-g-45204 spec.

Mil-std (military Standard):