

View Online at <https://aerobasegroup.com/nsn/5935-01-256-6727>

Body Style:

Straight type

Overall Length:

5.650 inches

Overall Height:

0.764 inches

Overall Width:

0.250 inches

Environmental Protection:

Shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.100 inches

Distance Between Mounting Facility Centers:

5.400 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Guide Design And Location:

D shape socket left-hand bottom at 9 oclock and d shape pin right-hand top at 9 oclock

Included Contact Quantity:

90 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.090 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.