

View Online at <https://aerobasegroup.com/nsn/5935-01-256-9563>

**Body Style:**

Straight shape w/clamp

**Overall Diameter:**

3.312 inches

**Environmental Protection:**

Heat resistant and salt water resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

4 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

30.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 single mating end all contact groupings

**Contact Maximum Frequency Rating:**

0.06 kilohertz single mating end all contact groupings

**Polarization Method:**

Contact

**Connector Locking Method:**

Friction

**Connector Cable Strain Relief Method:**

Finger grip

**Terminal Location:**

Side single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Terminal Type:**

Screw single mating end all contact groupings

**Included Contact Quantity:**

3 single mating end 2nd contact grouping

**Test Data Document:**

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81348-w-c-596/129 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0