

View Online at <https://aerobasegroup.com/nsn/5935-01-257-0120>

**Body Style:**

Straight type

**Overall Length:**

5.650 inches

**Overall Height:**

0.814 inches

**Overall Width:**

0.250 inches

**Environmental Protection:**

Vibration resistant and thermal shock resistant

**Unthreaded Mounting Hole Diameter:**

0.100 inches

**Distance Between Mounting Facility Centers:**

5.400 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Nickel single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Pin single mating end single contact grouping

**Guide Design And Location:**

D shape socket left-hand top at 3 oclock and d shape pin right-hand bottom at 3 oclock

**Included Contact Quantity:**

90 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.090 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0