# NSN 5935-01-257-1201

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-257-1201

# Thread Class:

2a and 2b

# **Thread Direction:**

Right-hand and right-hand

# Body Style:

Straight shape, internal coupling

## **Overall Length:**

0.402 inches

#### **Overall Diameter:**

0.312 inches

## **Environmental Protection:**

Vibration resistant and shock resistant

#### **Threaded Device Type:**

Coupling facility

#### Mating End Quantity:

2

#### **Contact Position Arrangement Style:**

Sma all mating ends

# **Contact Removability:**

Removable all mating ends single contact grouping

## Shell Type:

Solid

## **Connector Locking Method:**

Externally threaded shell

## Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

## Thready Qty Per Inch (tpi):

36 and 36

## Thread Size:

0.250 inches and 0.250 inches

## **Contact Material:**

Copper alloy all mating ends single contact grouping

## **Contact Surface Treatment:**

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

## **Insert Material:**

Plastic polytetrafluoroethylene all mating ends

# **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, gr c or d military specification 1st treatment response all mating ends single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

#### Shell Material:

Steel comp 302 or steel comp 303 or steel comp 304

# NSN 5935-01-257-1201

Connector Adapter - Page 2 of 2

---

No



**Shell Surface Treatment:** Passivate **Shell Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Shell Material Specification:** Qq-s-764 federal specification single material response or astm-a-582 assn standard single material response **Insert Material Specification:** Mil-p-19468 military specification single material response all mating ends **Included Contact Quantity:** 1 2nd mating end single contact grouping **Included Contact Type:** Coaxial socket 1st mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.010 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns and uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.