

View Online at <https://aerobasegroup.com/nsn/5935-01-257-2111>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.812 inches

**Overall Diameter:**

0.750 inches

**Environmental Protection:**

Vibration resistant and shock resistant and corrosion resistant and moisture resistant and pressure proof

**Cable Entrance Diameter:**

Between 0.437 inches and 0.447 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Tnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Compression nut

**End Application:**

6940-01-109-7041 transmitter, countermeasures training signal

**Thready Qty Per Inch (tpi):**

28

**Thread Size:**

0.438 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping

**Contact Surface Treatment:**

Copper single mating end single contact grouping and gold single mating end single contact grouping

**Insert Material:**

Plastic fluorocarbon single mating end

**Contact Surface Treatment Specification:**

Mil-c-14550 military specification 1st treatment response single mating end single contact grouping and mil-g-45204, type 1, grade c military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Contact Material Specification:**

Qq-b-825 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Material Specification:**

Qq-d-626, composition 22 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-14550 spec.