

View Online at <https://aerobasegroup.com/nsn/5935-01-257-5928>

Body Style:

Straight type

Overall Length:

4.900 inches

Overall Height:

0.645 inches

Overall Width:

0.400 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

4.650 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Glass single mating end and plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin left-hand at 9 o'clock and d shape socket right-hand at 9 o'clock

Insert Material Specification:

Mil-m-14 military specification all material responses single mating end

Included Contact Quantity:

122 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material And Weight:

0.244 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.