# NSN 5935-01-257-5930



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-257-5930 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.937 inches **Overall Diameter:** 1.328 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant **Distance From Mounting Shoulder To Front Face:** 0.687 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 27-30 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Detent Thready Qty Per Inch (tpi): 18

**Thread Size:** 

1.125 inches **Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

# NSN 5935-01-257-5930

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Rubber synthetic single mating end and plastic single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

#### **Terminal Type:**

Solder well single mating end single contact grouping

### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

**Shell Material:** 

Steel

**Shell Surface Treatment:** 

Tin and cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416 federal specification 2nd treatment response

**Included Contact Quantity:** 

91 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.091 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.