

View Online at <https://aerobasegroup.com/nsn/5935-01-257-8256>

Thread Class:

2b and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape w/flange

Overall Length:

Between 1.920 inches and 1.990 inches

Overall Height:

0.687 inches

Overall Width:

0.687 inches

Environmental Protection:

Thermal shock resistant and vibration resistant and shock resistant and moisture resistant

Unthreaded Mounting Hole Diameter:

Between 0.097 inches and 0.107 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.500 inches

Distance From Mounting Shoulder To Front Face:

1.295 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Tnc all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Frequency Rating:

18000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring and externally threaded shell

Thready Qty Per Inch (tpi):

28 and 28

Thread Size:

0.438 inches and 0.438 inches

Contact Material:

Copper alloy 173 all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and copper all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification 1st treatment response all mating ends single contact grouping and mil-c-14550, cl 4 military specification 2nd treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-c-530, 1/2 hard federal specification single material response all mating ends single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35, type 4 federal specification single treatment response

Shell Material Specification:

Astm-a-582, condition a assn standard single material response

Insert Material Specification:

L-p-403 federal specification single material response all mating ends

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.