NSN 5935-01-257-9598

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-257-9598

Body Style:
Straight type
Overall Length:
2.270 inches
Overall Height:
0.464 inches
Overall Width:
0.351 inches
Environmental Protection:
Thermal shock resistant and corrosion resistant and moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.096 inches
Distance Between Mounting Facility Centers:
2.000 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
51 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass fiber single mating end or plastic polyester single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping
Criticality Code Justification:
Zzzy
Terminal Type:
Pin single mating end single contact grouping

NSN 5935-01-257-9598

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Shell Material Specification:
Qq-a-591 federal specification single material response or qq-a-200 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-m-24519 military specification single material
response single mating end
Included Contact Quantity:
51 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo3754
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.051 gold grains, troy
Precious Material:
Gold
Reference Number Differentiating Characteristics:
Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No