## NSN 5935-01-257-9779

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-257-9779

**Body Style:** 

Straight shape, rectangular

**Overall Length:** 

Between 0.913 inches and 0.933 inches

**Overall Height:** 

Between 1.340 inches and 1.360 inches

**Overall Width:** 

Between 2.865 inches and 2.885 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.495 inches and 2.505 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

104 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Included Contact Quantity:** 

104 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact plating gold

**Precious Material:** 

Gold

**Test Data Document:** 

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-c-28748/10 government specification

**Departure From Cited Designator:** 

Shell type and polarization per ms17779-1w

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5935-01-257-9779

Electrical Receptacle Connector - Page 2 of 2



			on:	

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.