

View Online at <https://aerobasegroup.com/nsn/5935-01-258-2137>

**Body Style:**

Angle, shape, internal coupling

**Overall Length:**

1.610 inches

**Overall Height:**

1.090 inches

**Overall Diameter:**

0.570 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and thermal shock resistant

**Cable Entrance Diameter:**

0.206 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Compression nut

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold

**Shell Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold

**Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.