NSN 5935-01-258-7429

Thread Class: 2a and 2b

Right-hand **Body Style:**

Thread Direction:

Electrical Plug Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-258-7429

| Hood, top opening w/clamp |
|--|
| Overall Length: |
| 1.250 inches |
| Overall Width: |
| 0.500 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 14 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, top opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Cable Opening Length: |
| 0.480 inches |
| Cable Opening Width: |
| 0.437 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum |
| Shell Surface Treatment: |
| Anodize |
| Shell Material Specification: |
| Qq-a-250 federal specification single material response |
| Insert Material Specification: |
| Mil-m-14, ty gdi-30f or ty sdg-f military specification single material response single mating end |
| |
| |

NSN 5935-01-258-7429

Electrical Plug Connector Body - Page 2 of 2



| Thread Series Designator: |
|------------------------------|
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |

Mil-m-14 spec.