# NSN 5935-01-259-1271

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-259-1271

Body Style:
Straight type
Overall Length:
6.400 inches
Overall Height:
0.637 inches
Overall Width:
0.350 inches
Environmental Protection:
Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
6.150 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 125.0 degrees celsius
Terminal Location:

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Pin single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

# NSN 5935-01-259-1271

Electrical Receptacle Connector - Page 2 of 2



### **Guide Design And Location:**

D shape socket left-hand at 3 oclock and d shape pin right-hand at 3 oclock

## **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

## **Included Contact Quantity:**

160 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.160 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.