NSN 5935-01-259-1277

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-259-1277 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 6.400 inches **Overall Height:** 0.550 inches **Overall Width:** 0.490 inches **Environmental Protection:** Vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 6.150 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 3 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end 1st contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method: Operating Tempurature Rating:** Between -65.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): **Thread Size:** 0.112 inches

Terminal Location:

Side single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

NSN 5935-01-259-1277

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end 1st contact grouping
Terminal Type:
Pin single mating end 1st contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end 1st contact grouping
Insert Material Specification:
Mil-m-24519 military specification single material response single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
159 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.159 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.